

Vsuvka KAMLOK typ A - samec s vnitřním závitem

Název	Závít	Kód	Hmotnost(kg)	Těsnění	Materiál
050	ISO228-½"	050A.SS	0.07	PTFE	SS
075	ISO228-¾"	075A.SS	0.11	PTFE	SS
100	ISO228-1"	100A.SS	0.15	PTFE	SS
125	ISO228-1¼"	125A.SS	0.24	PTFE	SS
150	ISO228-1½"	150A.SS	0.32	PTFE	SS
200	ISO228-2"	200A.SS	0.42	PTFE	SS
250	ISO228-2½"	250A.SS	0.71	PTFE	SS
300	ISO228-3"	300A.SS	0.73	PTFE	SS
400	ISO228-4"	400A.SS	1.42	PTFE	SS
500	ISO228-5"	500A.SS	1.92	PTFE	SS
600	ISO228-6"	600A.SS	3.17	PTFE	SS
800	ISO228-8"	800A.SS	2.31	PTFE	SS
1000	ISO228-10"	-	-	PTFE	SS
1200	ISO228-12"	-	-	PTFE	SS

050	ISO228-½"	050A.AL	0.02	NBR	AL
075	ISO228-¾"	075A.AL	0.04	NBR	AL
100	ISO228-1"	100A.AL	0.05	NBR	AL
125	ISO228-1¼"	125A.AL	0.09	NBR	AL
150	ISO228-1½"	150A.AL	0.11	NBR	AL
200	ISO228-2"	200A.AL	0.15	NBR	AL
250	ISO228-2½"	250A.AL	0.24	NBR	AL
300	ISO228-3"	300A.AL	0.27	NBR	AL
400	ISO228-4"	400A.AL	0.58	NBR	AL
500	ISO228-5"	500A.AL	0.90	NBR	AL
600	ISO228-6"	600A.AL	0.84	NBR	AL
800	ISO228-8"	800A.AL	2.31	NBR	AL
1000	ISO228-10"	-	-	NBR	AL
1200	ISO228-12"	-	-	NBR	AL

050	ISO228-½"	050A.MS	0.07	NBR	MS
075	ISO228-¾"	075A.MS	0.10	NBR	MS
100	ISO228-1"	100A.MS	0.15	NBR	MS
125	ISO228-1¼"	125A.MS	0.20	NBR	MS
150	ISO228-1½"	150A.MS	0.29	NBR	MS
200	ISO228-2"	200A.MS	0.35	NBR	MS
250	ISO228-2½"	250A.MS	0.72	NBR	MS
300	ISO228-3"	300A.MS	0.73	NBR	MS
400	ISO228-4"	400A.MS	1.48	NBR	MS
500	ISO228-5"	500A.MS	1.79	NBR	MS
600	ISO228-6"	600A.MS	3.38	NBR	MS
800	ISO228-8"	-	7.36	NBR	MS
1000	ISO228-10"	-	-	NBR	MS
1200	ISO228-12"	-	-	NBR	MS

050	ISO228-½"	050A.PP	0.01	NBR	PP
075	ISO228-¾"	075A.PP	0.02	NBR	PP
100	ISO228-1"	100A.PP	0.03	NBR	PP
125	ISO228-1¼"	125A.PP	0.05	NBR	PP
150	ISO228-1½"	150A.PP	0.06	NBR	PP
200	ISO228-2"	200A.PP	0.09	NBR	PP
250	ISO228-2½"	250A.PP	0.14	NBR	PP
300	ISO228-3"	300A.PP	0.18	NBR	PP
400	ISO228-4"	400A.PP	0.36	NBR	PP
500	ISO228-5"	500A.PP	-	NBR	PP
600	ISO228-6"	600A.PP	-	NBR	PP



KAMLOK typu A je možné dodat i se závitem NPT nebo BSP