

Vsuvka KAMLOK typ A - samec s vnitřním závitem

Kód	DN	Závít	Hmotnost(kg)	Těsnění	Materiál
050A.SS	15	ISO228-1/2"	0.07	PTFE	SS
075A.SS	20	ISO228-3/4"	0.11	PTFE	SS
100A.SS	25	ISO228-1"	0.15	PTFE	SS
125A.SS	32	ISO228-1 1/4"	0.24	PTFE	SS
150A.SS	40	ISO228-1 1/2"	0.32	PTFE	SS
200A.SS	50	ISO228-2"	0.42	PTFE	SS
250A.SS	65	ISO228-2 1/2"	0.71	PTFE	SS
300A.SS	80	ISO228-3"	0.73	PTFE	SS
400A.SS	100	ISO228-4"	1.42	PTFE	SS
500A.SS	125	ISO228-5"	1.92	PTFE	SS
600A.SS	150	ISO228-6"	3.17	PTFE	SS
800A.SS	200	ISO228-8"	2.31	PTFE	SS
-	250	ISO228-10"	-	PTFE	SS
-	300	ISO228-12"	-	PTFE	SS

050A.AL	15	ISO228-1/2"	0.02	NBR	AL
075A.AL	20	ISO228-3/4"	0.04	NBR	AL
100A.AL	25	ISO228-1"	0.05	NBR	AL
125A.AL	32	ISO228-1 1/4"	0.09	NBR	AL
150A.AL	40	ISO228-1 1/2"	0.11	NBR	AL
200A.AL	50	ISO228-2"	0.15	NBR	AL
250A.AL	65	ISO228-2 1/2"	0.24	NBR	AL
300A.AL	80	ISO228-3"	0.27	NBR	AL
400A.AL	100	ISO228-4"	0.58	NBR	AL
500A.AL	125	ISO228-5"	0.90	NBR	AL
600A.AL	150	ISO228-6"	0.84	NBR	AL
800A.AL	200	ISO228-8"	2.31	NBR	AL
-	250	ISO228-10"	-	NBR	AL
-	300	ISO228-12"	-	NBR	AL

050A.MS	15	ISO228-1/2"	0.07	NBR	MS
075A.MS	20	ISO228-3/4"	0.10	NBR	MS
100A.MS	25	ISO228-1"	0.15	NBR	MS
125A.MS	32	ISO228-1 1/4"	0.20	NBR	MS
150A.MS	40	ISO228-1 1/2"	0.29	NBR	MS
200A.MS	50	ISO228-2"	0.35	NBR	MS
250A.MS	65	ISO228-2 1/2"	0.72	NBR	MS
300A.MS	80	ISO228-3"	0.73	NBR	MS
400A.MS	100	ISO228-4"	1.48	NBR	MS
500A.MS	125	ISO228-5"	1.79	NBR	MS
600A.MS	150	ISO228-6"	3.38	NBR	MS
-	200	ISO228-8"	7.36	NBR	MS
-	250	ISO228-10"	-	NBR	MS
-	300	ISO228-12"	-	NBR	MS

050A.PP	15	ISO228-1/2"	0.01	NBR	PP
075A.PP	20	ISO228-3/4"	0.02	NBR	PP
100A.PP	25	ISO228-1"	0.03	NBR	PP
125A.PP	32	ISO228-1 1/4"	0.05	NBR	PP
150A.PP	40	ISO228-1 1/2"	0.06	NBR	PP
200A.PP	50	ISO228-2"	0.09	NBR	PP
250A.PP	65	ISO228-2 1/2"	0.14	NBR	PP
300A.PP	80	ISO228-3"	0.18	NBR	PP
400A.PP	100	ISO228-4"	0.36	NBR	PP
500A.PP	125	ISO228-5"	-	NBR	PP
600A.PP	150	ISO228-6"	-	NBR	PP



KAMLOK typu A je možné dodat i se závitem NPT nebo BSP